


ActiveRFID: Towards a Self-Powered Wireless Sensing Platform

Mervin John, Jesse Richmond, Louis Alarcon, Wen Li, Tsung-Te Liu, Wenting Zhou, Kimiya Hajkazemshirazi, Kenichi Agawa, Michael Mark, Massimo Alioto, Seth Sanders, Jan Rabaey

Wireless Sensing – Today

Wireless sensor networks:


- Cost, size and power consumption goals for single devices within technology reach
- Communication distances from cm's to 10's of meters



UCB PicoCube


Drawbacks:

- Need network support to be functional – causes **major deployment and reliability issues**
- **Energy still a major issue**




"Self - Contained" Active RFID

- Combines advantages of WSN & passive RFID tags:
 - With power source, enable interrogation from distances >10m
 - Compatible with existing RFID protocols
 - Easy deployment, low cost, secure...
- Opens the door for new applications:
 - Enables querying for portable mobile devices (e.g. cell phone) or from a deployed network (WiFi)
- Tag is self-contained, harvesting energy from solar cell.



Specifications (Target)






- Fully integrated
- Postage stamp size
- Communication range >10 m
- Datarate of 100 kbps
- Compatible with RFID link and MAC specification

- Can operate indefinitely (for 24 hours/day) from single solar cell – **average power dissipation on the order of μ Ws**

Enables querying from portable mobile devices (e.g. cell phones), or from a deployed network

Powering the Active RFID

- Self-powered Active RFID Tag
 - **Self-contained** (postage stamp footprint but only mm's thick)
 - **Fully integrated** IC (single die)
 - **Small solar cell** harvests enough energy for 24 hour operation



Solar Cell

- 2cmx1cm
- **10 μ W** avg (Indoor)
- $V_{oc} = 2.4V$, $I_{sc} = 10\mu A$

Printed Battery


- 1cmx1cm
- $V_{bat} \sim 1.1-1.8V$
- Integration w/ substrate

Loads (on Single Die)

- 50 μ W RX
- 1mW TX
- **0.5V** Logic
- On-chip power management



System Power Modes



3 orders of magnitude difference within power!


Integrated Power Management

On-Chip Integrated Caps

- $\sim 0.3\text{mm}^2$
- Multi-topology for coarse regulation
- Multiple cells interleaved to reduce clock ripple

Control Logic

- Regulation Scheme
- Dynamic frequency & switch Scaling



Multiple Supply Rails

- 500mV V_{dd}
- Ripple, Current specs vary


Multi-Mode Operation

- Blocks turned off to reduce leakage/standby current
- Wide output loads (3uA \rightarrow 100uA \rightarrow 10mA)

Analog Blocks

- Voltage & Current references
- Low-dropout regulator for finer regulation

Chip Layout and Floorplan





Chip size: 2mm x 2mm

Utilizes full-custom layout and design for the radios and power, generated standard cells for digital.

Sent to Fab: **May 2010**

Return from Fab: **Sept 2010**

Hot off the Press: Chip Die Photo



2 mm

We have developed a ActiveRFID Platform

- Enables small active RFID nodes powered purely by energy scavenging with less 10 μ W of average power
- Are easy to deploy and can use existing infrastructure
- Can communicate over more than 10 m indoors
- Fully integrated design contains all power management and communication circuits
- Testing underway

Mervin John (mervin@eecs.berkeley.edu)

Jesse Richmond, Louis Alarcon, Wen Li, Tsung-Te Liu, Wenting Zhou, Kimiya Hajkazemshirazi, Kenichi Agawa, Michael Mark, Massimo Alioto, Jan Rabaey

Acknowledgements

- California Energy Commission
- STMicroelectronics
- Avago Technologies
- GSRC
- SRC/Freescale
- BWRC Member Companies